

CRITCHLEY ADSL TRANSFORMERS 6A304



- For use with the following Chipsets:

Alcatel Microelectronics	MTK 20131
---------------------------------	------------------

- Alcatel reference number : 1AB 01965 0026
- Designed for Optimum performance in a small footprint.

ELECTRICAL SPECIFICATION*						
Inductance @ 10 kHz 0.1 Vrms.	Inductance @ 10 kHz 0.1 Vrms.	Turns Ratio	DC Resistance (max.)		Isolation Voltage (for 2 secs.)	
2 - 6	2 - 3 (s/c 5-6)	2 - 6 : 5 - 3	2 - 6	5 - 3	2 - 5	2+5 : Core
222 - 255 μH	890 - 985 μH	1 : 1	0.7 Ω	0.7 Ω	500 Vrms	500 Vrms

* At 23°C

SCHEMATIC	MECHANICAL SPECIFICATION
<p style="text-align: center;">Turns Ratio 1 : 1</p> <p>This component is tested to : IEC 68-2-14:1984 Nb (temperature range: -40°C to +125°C).</p> <p>Approximate Weight.....3 grams</p>	<p style="text-align: center; color: red;">Through Hole Style - 6A304</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>TOP VIEW</p> </div> <div style="text-align: center;"> <p>SIDE VIEW</p> </div> <div style="text-align: center;"> <p>PIN LAYOUT</p> </div> </div> <p style="text-align: center;">Dimensions in mm</p>

Pontiac Coil – Europe Ltd.

PO Box 246
Queens Drive Industrial Estate
Nottingham NG2 1NQ

United Kingdom

Tel: +44 (0) 115 986 1126
Fax: +44 (0) 115 986 0563

Pontiac Coil, Inc.

5800 Moody Drive
Clarkston
Michigan 48348

USA

Tel: +1 248 922 2203
Fax: +1 248 922 1315

Local Distributors available in:

**Australia, Finland, Israel,
Italy, Malaysia, Norway, Singapore,
Sweden and Taiwan.**

For details contact Pontiac Coil - Europe Ltd.

sales@pontiaccoil.co.uk

www.pontiaccoil.co.uk